



Accessories for JES-301



TECHNICAL DATA

Part N°	FLANGE ADAPTER	MATERIAL	
35.08015	DN65/PN6 to 2 1/2", 150 lbs	SS316	Threaded bolts 4 x M12 and 4 x M16
35.08025	DN65/PN6 to 3" ANSI, 150 lbs	SS316	Threaded bolts 4 x M12 and 4 x M16
35.08170	DN65/PN6 to 3" ANSI, 300 lbs, RF	SS316	Threaded bolts 4 x M12 and 8 x M20
35.08027	DN65/PN6 to DN25/PN10; with female 1/2"-14 NPT	SS316L	Threaded bolts 4 x M12 and 4 x M12
35.08155	DN65/PN6 to DN50/PN6	SS316Ti	Threaded bolts 4 x M12 and 4 x M16
35.08035	DN65/PN6 to DN80/PN6	SS316	Threaded bolts 4 x M12 and 4 x M16
35.08150	DN65/PN6 to DN80/PN10-16, RF	SS316	Threaded bolts 4 x M12 and 8 x M16
35.08045	DN65/PN6 to DN100/PN16	SS316	Threaded bolts 4 x M12 and 8 x M16
35.08040	DN65/PN6 to DN100/PN25	SS316	Threaded bolts 4 x M12 and 8 x M20
35.08130	DN65/PN6 to JIS10K-40	SS316L	Threaded bolts 4 x M12 and 4 x M16
35.08110	DN65/PN6 to ANSI 1", 150 lbs	SS316	Threaded bolts 4 x M12 and 4 x M12
35.08070	DN65/PN6 to ANSI 2", 150 lbs	SS316	Threaded bolts 4 x M12 and 4 x M16
35.08145	DN65/PN6 to 2" ANSI, 300 lbs	SS316	Threaded bolts 4 x M12 and 8 x M16
35.08100	DN65/PN6 to 4" ANSI, 150 lbs, RF	SS316	Threaded bolts 4 x M12 and 4 x M20
35.08105	DN65/PN6 to 4" ANSI, 150 lbs, RF for JER-EH	SS316	Threaded bolts 4 x M12, 66 mm long and 8 x M16
35.08120	DN65/PN6 to 4" ANSI, 150 lbs, FF	SS316	Threaded bolts 4 x M12 and 4 x M16
35.08080	DN65/PN6 to 4" ANSI, 300 lbs	SS316	Threaded bolts 4 x M12 and 8 x M20
35.08090	DN65/PN6 to 6" ANSI, 150 lbs, RF	SS316	Threaded bolts 4 x M12 and 8 x M20
35.08140	ANSI 2" 150 lbs to ANSI 4", 150 lbs	SS316	Threaded bolts 4 x M16 and 8 x M16
35.08192	Screw-in adapter flange, G3" to DN25/PN40	SS316	for screw in mounting
35.08190	Screw-in adapter flange, G3" to DN65/PN6	SS316	for screw in mounting
35.01410	Calibration/Back purge flange DN65/PN6	SS316	Sampling-/ calibration port 1/8" NPTi
35.01411	Calibration/Back purge flange ANSI 2", 150 lbs	SS316	Sampling-/ calibration port 1/8" NPTi
35.00969	Weld-in flange (process flange), DN65/PN6, length 200 mm	SS316Ti (1.4571)	
35.01402	Thermal spacer 2 x DN65/PN6, length 200 mm	SS316	4 holes for M12 per flange
35.01401	Thermal spacer 2 x DN65/PN6, length 300 mm	SS316	4 holes for M12 per flange

TECHNICAL DATA

Part N°	ACCESSORIES FOR GAS CONNECTIONS (SS316)
35.90120	Union 6 mm to 6 mm tube
35.90121	Reduction union 6 mm to 8 mm tube
35.90122	Reduction union 6 mm to 10 mm tube
35.90123	Reduction union 6 mm to 12 mm tube
35.90124	Reduction union 6 mm to 1/4" mm tube
35.90125	Reduction union 6 mm to 5/6" mm tube
35.90126	Reduction union 6 mm to 3/8" mm tube
35.90127	Reduction union 6 mm to 1/2" mm tube
35.90094	Non-return valve 1/8" (200 °C), Viton®
35.90068	Non-return valve 1/8" (320 °C), Kalrez®
35.90097	Non-return valve 3/8" (200 °C), Viton®
35.90096	Non-return valve 3/8" (320 °C), Kalrez®
35.90080	Male connector for 6 mm tube, 1/8" NPT
35.90081	Male connector for 8 mm tube, 1/8" NPT
35.90086	Male connector for 10 mm tube, 1/8" NPT
35.90130	Male connector for 12 mm tube, 1/8" NPT
35.90082	Blind plug 1/8" NPT male thread
35.90083	Male connector for 1/4" tube, 1/8" NPT
35.90131	Male connector for 5/6" tube, 1/8" NPT
35.90084	Male connector for 3/8" tube, 1/8" NPT
35.90132	Male connector for 1/2" tube, 1/8" NPT
35.90085	Elbow connector for 6 mm tube, 1/8" NPT
35.90098	Y-connector for 2 x 6 mm pipe, 1/8" NPT, for JES-301 with 2 x sample outlet
35.90008	O-ring removal tool

Part N°	ACCESSORIES FOR HEATED SAMPLE LINES
35.00970	PG42 fitting complete
35.00980	Mounting clamp (35 to 50 mm)
35.00981	Mounting clamp (58 to 61 mm)
68.04914	Heat shrink cable entry seal, 19 – 42 mm, drill hole 50.8 mm
K1047164	Heat shrink cable entry seal, 35 – 70 mm, drill hole 70.48 mm